

# 0015

## 15" Planer with Byrd<sup>®</sup> Cutterhead



SERRATED  
STEEL infeed  
roller.



BUILT-IN mobile base.



GENUINE BYRD<sup>™</sup>  
cutterhead comes  
standard.

Model No.	0015
Stock No. (3HP, 1Ph, Byrd)	0015.201
Maximum Stock Width	15"
Maximum Depth of Cut	1/8"
Maximum Stock Thickness	6"
Minimum Stock Thickness	1/8"
Minimum Stock Length	6"
Dust Port Diameter	4"
Infeed Roller Diameter	2" - Solid Serrated Steel
Feed Speeds	16/30 FPM
Bed Rollers	2
Table Size	15" L x 20" W
Table Size w/Extension Wings	15" L x 60" W
Table Height	30"
Cutterhead Diameter	3"
Cutterhead Speed	5,000 RPM
Cutterhead	Byrd
Number of Byrd Inserts	75
Infeed Extension Table Size	20"
Outfeed Extension Table Size	20"
Gross Weight	430 lbs
Motor (1Ph)	3HP, 1Ph 230V Only (13 AMPS)
Gross Weight	430 lbs

- Authentic BYRD Shelix cutter head allows smooth cuts.
- Carbide inserts are indexed for quick changing.
- Heavy cast iron construction throughout.
- Foldable metal extension wings with built-in rollers.
- Four-post design ensures head alignment regardless of stock height.
- Large hand wheel allows easy height adjustment.
- Serrated steel infeed roller provides smooth feeding.
- 2-speed gear box provides the perfect feed rate.
- Polished built-in table roller assists movement of rough stock.
- Table remains at the same height allowing extension support to be easily added.
- Top mounted motor includes magnetic controls for added safety.
- Built-in casters with locks for easy mobility.
- 4" dust chute easily handles chip removal.
- Matched 3 V-belt drive smoothly transfers power to drive train and cutter head.
- Powerful TEFC 3HP single-phase motor.
- CSA listed.