

# 4016

## 10" Table Saw, 5HP



- Large precision ground table provides a stable work surface.
- Cast iron base offers a steady platform.
- Fully enclosed cabinet and blade dust shroud for better dust management.
- Precision ground 1" arbor.
- Wide stance trunnion features a left tilt blade.
- Poly V-belt drive smoothly transfers power to the blade.
- Hydraulic assisted blade lift mechanism for easy movement.
- Large chrome hand wheels allow easy adjustments.
- Includes digital readout of blade tilt.
- Riving knife splitter for added safety against kick-back.
- Optimus T-square fence available in 36" or 52" capacity.
- 36" includes (2) cast iron wings.
- Optional 52" includes wood side table and (1) cast iron wing.
- Optional rear support table available.
- Magnetic controls with emergency off switch.
- Powerful TEFC motor available in single or three-phase.
- Miter gauge included.
- Blade not included.

Model No.	4016
Stock No.	4016.003 (5HP, 1Ph)
Stock No.	4016.004 (5HP, 3Ph)
Blade Diameter	10"
Arbor Diameter	5/8"
Maximum Width of Dado	13/16"
Maximum Depth of Cut at 90°	3"
Maximum Depth of Cut at 45°	2-1/4"
Maximum Cut to the Right of Blade	36" / 52" with side table
Maximum Cut to the Left of Blade	12"
Dust Port Diameter	4" Ø
Table Dimensions w/Extensions	27"D x 33 1/3"W
Wing Size	27" x 12"
Table Height	36"
Blade Tilt	Left
Arbor Speed	3,450 RPM
Motor (1Ph)	5HP, 220V Only (18 Amps)
Motor (3Ph)	5HP, 220V or 440V* Prewired 220V (12 Amps 220V, 6 Amps 440V)
Overall Dimensions	74"L x 32-1/2"W x 40"H
Gross Weight	650 lbs



Pictured with optional 52" rail, side and rear tables.



A BLADE ENCOMPASSING DUST shroud joined with the standard 4" outlet.

\*Optional 440/460 volt available special order only. Additional cost/parts may apply.



THE 4016 comes standard with a blade guard and a riving knife.



A HYDRAULICALLY assisted worm/pinion gear, blade lift mechanism.



MITER GAUGE included.



A DIGITAL ANGLE METER takes the guess work out of mitre cuts.