

# 4045

## 12" Table Saw



Pictured with optional 52" rail, side and rear tables.



<b>Model No.</b>	<b>4045</b>
Stock No.	4045.003 (5HP, 1Ph)
Stock No.	4045.004 (7.5HP, 3Ph)
Blade Diameter	12"
Arbor Diameter	1"
Maximum Width of Dado	13/16"
Maximum Depth of Cut at 90°	4"
Maximum Depth of Cut at 45°	2-2/3"
Maximum Cut to the Right of Blade	36" / 52" with side table
Maximum Cut to the Left of Blade	12"
Dust Port Diameter	4" Ø
Table Dimensions w/Extensions	30-3/4"D x 48-1/2"W
Wing Size	30-3/4" x 12"
Table Height	36"
Blade Tilt	Left
Arbor Speed	3,450 RPM
Motor (1Ph)	5HP, 220V Only
Motor (3Ph)	7.5HP, 220V/440V* Prewired 220V
Overall Dimensions	75"L x 45"W x 41"H
Gross Weight	772 lbs

- Large precision ground table provides a stable work surface.
- Cast iron base offers a steady platform.
- Fully enclosed cabinet and blade dust shroud for better dust management.
- Precision ground 1" arbor.
- Wide stance trunnion features a left tilt blade.
- Poly V-belt drive smoothly transfers power to the blade.
- Hydraulic assisted blade lift mechanism for easy movement.
- Large chrome hand wheels allow easy movement.
- Includes digital readout of blade tilt.
- Riving knife splitter for added safety against kick-back.
- Optimus T-square fence available in 36" or 52" capacity.
- 36" includes (2) cast iron wings.
- Optional 52" includes wood side table and (1) cast iron wing.
- Optional rear support table available.
- Magnetic controls with emergency off switch.
- Powerful TEFC motor available in single or three-phase.
- Miter gauge included
- Blade not included.



**A BLADE ENCOMPASSING DUST** shroud joined with the standard 4" outlet.

\*Optional 440/460 volt available special order only. Additional cost/parts may apply.



**THE 4045 COMES** standard with a blade guard and a riving knife.



**A DIGITAL ANGLE METER** takes the guess work out of mitre cuts.



**HYDRAULICALLY ASSISTED** worm/pinion gear, blade lift mechanism.



**MITER GAUGE** included.