

5150

21-Spindle Single Unit Line Boring

- Large table provides an excellent work surface.
- Can be used in the horizontal or vertical position.
- Quick connect drill chucks assist in quick tool changes.
- 3M rule gauge with 4-adjustable stops is included.
- Two guide pins are provided for repetitive operations.
- Mechanical DRO for precise boring head adjustment.
- Central control panel allows quicker operation.
- Convenient foot pedal controls the entire boring cycle.
- Adjustable drilling depth includes 6-positions for added convenience.
- Drill speed stabilizer allows smooth initial contact for a better finish.
- Powerful 2.5HP single phase motor.



STEEL GEARS in an aluminum housing provide longer life. Quick change chucks allow easy bit change.



ACCURATE ADJUSTMENT OF BORING UNIT and speed stabilizer provides smooth feeding against the workpiece.

Model No.	5150
Stock No.	5150.001
Table Size	34-1/4" x 19-1/4"
Max. Drilling Depth	3"
Spindle Speed	2800 RPM
Distance Between Center	32mm
Compress Air Required	6-8 kg/cm2
Number of Spindles Per Boring Head	21
Quick Chuck	21 Pieces
Boring Head Adjustment	0-90°
Motors	2.5 HP, 1 Ph
Gross Weight	950 lbs
Overall Dimensions	30"L x 32"W x 48"H



THE BORING UNIT CAN be adjusted from horizontal to vertical drilling by pneumatic setting.