

5355 & 5385

25" & 37" Single-Head Wide Belt Sanders



- 75" belts give you longer life and less loading.
- Central control panel feature digital control for accurate stock height and removal.
- Heavy precision ground table gives a solid working surface.
- Power table height adjustment provides for a quick set-up.
- Variable speed feed motor allows precise adjustment for optimum results.
- Four post lift design assures accurate consistent results.
- Oscillating belt is controlled by an air sensor to prevent sanding lines.
- Platens are fully adjustable and can be removed.
- Multiple dust ports for efficient dust management.
- Independent motors run the sanding belt, feed conveyor, and table elevation for maximum power to each operation.




DIGITAL CONTROLS allow for accurate and quick thickness settings.



POWERFUL VARIABLE speed drive with reduction gear box.

Model No.	5355	5385
Stock No. (15HP, 3Ph)	5355.002	5385.002
Maximum Stock Width	25"	37"
Maximum Stock Thickness	5"	5"
Minimum Stock Thickness	1/8"	1/8"
Air Requirements	80 PSI	80 PSI
Exhaust Value Required	800 CFM	1,600 CFM
Dust Port	5" (x2)	5" (x3)
Abrasive Belt Dimensions	25"W x 75"L	37"W x 75"L
Main Motor	15HP, 3Ph, 220/440V* Prewired 220V (36.7 AMPS)	20HP, 3Ph, 220/440V* Prewired 220V
Conveyor Motor	1HP, 3Ph 220/440V Prewired 220V	1HP, 3Ph 220/440V Prewired 220V
Table Raising Motor	1/4HP	1/4HP
Gross Weight	1,985 lbs	2,425 lbs
Overall Dimensions	53"L x 46"W x 85"H	53"L x 58"W x 85"H



FOUR ELEVATING SCREWS eliminate table pivoting and ensure accuracy.

*Optional 440/460 volt available special order only.
Additional cost/parts may apply.