

# 5360, 5390 & 5395

## 25", 37" & 43" Double-Head Wide Belt Sanders



**DOUBLE  
HEAD** design.



- 75" belts give you longer life and less loading.
- Double head design allows removal and finish sanding in a single pass.
- Belt tracking is controlled by photo sensors for superior performance.
- Central control panel feature digital control for accurate stock height and removal.
- Heavy precision ground table gives a solid working surface.
- Power table height adjustment provides for a quick set-up.
- Variable speed feed motor allows precise adjustment for optimum results.
- Four post lift design assures accurate consistent results.
- Oscillating belt is controlled by an air sensor to prevent sanding lines.
- Platen is fully adjustable.
- Multiple dust ports for efficient dust management.
- Independent motors run the sanding belt, feed conveyor, and table elevation for maximum power to each operation.

Model No.	5360	5390	5395
Stock No.	5360.002 (15HP, 3Ph)	5390.002 (20HP, 3Ph)	5395.002 (25HP, 3Ph)
Maximum Stock Width	25"	37"	43"
Maximum Stock Thickness	6"	6"	6"
Minimum Stock Thickness	1/8"	1/8"	1/8"
Air Requirements	80 PSI	80 PSI	80 PSI
Dust Port Diameter	5" (x4)	5" (x6)	5" (x8)
Exhaust Value Required	800 CFM	1,600 CFM	1,900 CFM
Abrasive Belt Dimensions	25"W x 75"L	37"W x 75"L x	43"W x 75"L
Feed Speed	Variable, 15 - 49 FPM	Variable, 15 - 49 FPM	Variable, 15 - 49 FPM
Main Motor	15HP, 3Ph, 220/440V* Prewired 220V	20HP, 3Ph, 220/440V* Prewired 220V	25HP, 3Ph, 220/440V* Prewired 220V
Conveyor Motor	1HP, 3Ph 220/440V Prewired 220V	1HP, 3Ph 220/440V Prewired 220V	1HP, 3Ph 220/440V Prewired 220V
Table Height Motor/Digital Readout	1/4HP	1/4HP	1/4HP
Gross Weight	2,755 lbs	3,637 lbs	4,078 lbs
Overall Dimensions	63"L x 45.5"W x 86.5"H	52"L x 80"W x 75"H	63"L x 65"W x 86.5"H

\*Optional 440/460 volt available special order only.  
Additional cost/parts may apply.