

# 5392 & 5397

## 36" & 43" Double-Head Wide Belt Sanders



BACK VIEW

- 75" belts give you longer life and less loading.
- Double head design allows removal and finish sanding in a single pass.
- Belt tracking is controlled by photo sensors for superior performance.
- Central control panel feature digital control for accurate stock height and removal.
- Heavy precision ground table gives a solid working surface.
- Power table height adjustment provides for a quick set-up.
- Variable speed feed motor allows precise adjustment for optimum results.
- Four post lift design assures accurate consistent results.
- Oscillating belt is controlled by an air sensor to prevent sanding lines.
- Platens are fully adjustable and can be removed.
- Multiple dust ports for efficient dust management.
- Independent motors run the sanding belt, feed conveyor, and table elevation for maximum power to each operation.

DIGITAL CONTROLS allow for accurate and quick thickness settings.



HEAVY DUTY double head design.

Model No.	5392	5397
Stock No.	5392.002 (20/15HP, 3Ph)	5397.002 (30/20HP, 3Ph)
Maximum Stock Width	36"	43"
Maximum Stock Thickness	6"	6"
Minimum Stock Thickness	1/8"	1/8"
Table Height	37-1/2"	37-1/2"
Brush Roller Motor (One Set)	1/2HP	1HP
Dust Ports	5" x 2	5" x 2
Air Requirements	80 PSI	80 PSI
Abrasive Belt Dimensions	36"W x 75"L	43"W x 75"L
Main Motor (x2)	20HP/15HP, 3Ph, 220/440V * Prewired 220V	30HP/20HP, 3Ph, 220/440V* Prewired 220V
Conveyor Motor	2HP, 3Ph 220/440V Prewired 220V	3HP, 3Ph 220/440V Prewired 220V
Table Height Motor/Digital Readout	1/2HP	1/2HP
Net Weight	5,732 lbs	6,614 lbs

\*Optional 440/460 volt available special order only.  
Additional cost/parts may apply.