

# 7660

## Round Rod Milling Machine

- Highly efficient design for maximum production.
- Independent cutter head and feed motor provide unmatched performance with a maximum feed rate of 52 feet per minute.
- 4-feed rates allow greater versatility of material and applications.
- Feed can be reversed for quick stock removal in the case of a jam.
- Fully guarded hood provides a safe work station.
- Wide range of capacity from 3/8" to 2-3/8" with optional cutter sets.
- Includes 1" and 2" cutter.
- Built-in 4" dust port allows efficient dust management.
- Magnetic controls for safer operation.
- Powerful three phase 5HP TEFC cutter head and 2HP TEFC feed motor.



THE UNITS ARE DESIGNED FOR THE PERFECT PRODUCTION of round rods from square stock.



INCLUDES 1" & 2" cutter sets.

3/8", 3/4", 7/8", 1-1/4, 1-3/4, 2-1/4, 2-3/8" HSS Cutterheads available as optional.

<b>Model No.</b>	<b>7660</b>
Stock No.	7660.001
Cutting Capacity	3/8" - 2-3/8"
Cutter Set	1" & 2"
Minimum Length of Stock	12"
Cutterhead Drive Motor	5HP
Feed Motor	2HP
Cutterhead Speed	3,000 RPM
Feed Speeds	20, 30, 43, 53 FPM
Overall Dimensions (L x W x H/in.)	36-1/4 x 30 x 39-1/2"
Main Motor	5HP, 3Ph 220V
Gross Weight	805 lbs