

5300

SERIES

800-559-5065 | WWW.OLIVERMACHINERY.NET



A TRADITION OF INNOVATION™



WIDE BELT SANDERS

FOR A DEALER NEAR YOU, OR FOR MORE INFORMATION
CALL OLIVER MACHINERY AT 1-800-559-5065
OR VISIT WWW.OLIVERMACHINERY.NET

5355/5385

25" & 37" SINGLE HEAD WIDE BELT SANDERS



FEATURING

- Digital Thickness Controller
- Thickness Sensor
- Variable Speed Feed
- Fully Adjustable and Removable Platen
- Heavy Ground Table Supported by Four Elevating Screws
- Y-Delta Soft Start on Main Motor
- Infeed Support Roller 2 PCS with Support Bracket
- Pressure Shoe with Roller



LONGER LIFE

The 5355 & 5385 have 75" belts (most belt sanders are 60"), which gives you 20% more sanding area for better cooling, less loading and longer belt life.




DIGITAL CONTROLS allow for accurate and quick thickness settings; just dial in the stock height and how much you want to take off, and go.



POWERFUL VARIABLE speed drive with reduction gear box pulls even the highest stock through.

Model No.	5355	5385
Stock No. (15HP, 3Ph)	5355.003	5385.003
Maximum Stock Width	25"	37"
Maximum Stock Thickness	5"	5"
Minimum Stock Thickness	1/8"	1/8"
Air Requirements	80 PSI	80 PSI
Exhaust Value Required	800 CFM	1,600 CFM
Abrasive Belt Dimensions	75"L x 25"W	75"L x 37"W
Main Motor	15HP, 3Ph, 220/440V Prewired 220V (36.7 AMPS)	20HP, 3Ph, 220/440V Prewired 230V
Conveyor Motor	1HP, 1Ph, 220V Only (3.4 AMPS) 1HP, 3Ph 220/440V Prewired 220V	1HP, 1Ph, 220V Only 1HP, 3Ph 220/440V Prewired 220V
Table Height/Digital Readout	1/4HP (1.2 AMPS)	1/4HP
Gross Weight	1,985 lbs	2,425 lbs
Overall Dimensions	53"L x 46"W x 85"H	53"L x 58"W x 85"H



FOUR ELEVATING SCREWS eliminate table pivoting and ensure accuracy.

5360/90/95



25", 37" & 43" DOUBLE HEAD WIDE BELT SANDERS



FEATURING

- Digital Thickness Controller
- Photo Sensors for Tracking
- Variable Speed Feed
- Fully Adjustable and Removable Platen
- Heavy Ground Table Supported by Four Elevating Screws
- Y-Delta Soft Start on Main Motor
- Infeed Support Roller 2 PCS with Support Bracket
- Pressure Shoe with Roller



HEAVY DUTY double head configuration.



ADJUSTABLE air pressure inlet.

Model No.	5360	5390	5395
Stock No.	5360.003 (15HP, 3Ph)	5390.003 (20HP, 3Ph)	5395.003 (25HP, 3Ph)
Maximum Stock Width	25"	37"	43"
Maximum Stock Thickness	6"	6"	6"
Minimum Stock Thickness	1/8"	1/8"	1/8"
Air Requirements	80 PSI	80 PSI	80 PSI
Dust Port Diameter	5"	5"	5"
Exhaust Value Required	800 CFM	1,600 CFM	1,900 CFM
Abrasive Belt Dimensions	75"L x 25"W	75"L x 37"W	75"L x 43"W
Feed Speed	Variable, 15 - 49 FPM	Variable, 15 - 49 FPM	Variable, 15 - 49 FPM
Main Motor	15HP, 3Ph, 220/440V Prewired 220V	20HP, 3Ph, 220/440V Prewired 220V	25HP, 3Ph, 220/440V Prewired 220V
Conveyor Motor	1HP, 3Ph 220/440V Prewired 220V	1HP, 3Ph 220/440V Prewired 220V	1HP, 3Ph 220/440V Prewired 220V
Table Height Motor/Digital Readout	1/4HP	1/4HP	1/4HP
Gross Weight	2,755 lbs	3,637 lbs	4,078 lbs
Overall Dimensions	63"L x 45.5"W x 86.5"H	63"L x 57.5"W x 86.5"H	63"L x 65"W x 86.5"H

5392/5397



36" & 43" HEAVY DUTY DOUBLE HEAD WIDE BELT



FEATURING

- Digital Thickness Controller
- Photo Sensors for Tracking
- Variable Speed Feed
- Fully Adjustable and Removable Platen
- Heavy Ground Table Supported by Four Elevating Screws
- Y-Delta Soft Start on Main Motor
- Infeed Support Roller 2 PCS with Support Bracket
- Pressure Shoe with Roller
- Automatic Conveyor Belt Tracking
- Leveling Adjustment for Sanding Head
- Roller type: A-B (RUBBER ROLLER-PAD)

LONGER LIFE

The 5392 & 5397 have 75" belts (most belt sanders are 60"), which gives you 20% more sanding area for better cooling, less loading and longer belt life.

DIGITAL CONTROLS allow for accurate and quick thickness settings; just dial in the stock height and how much you want to take off, and go.



Model No.	5392	5397
Stock No.	5392.003 (20/15HP, 3Ph)	5397.003 (30/20HP, 3Ph)
Maximum Stock Width	36"	43"
Maximum Stock Thickness	6"	6"
Minimum Stock Thickness	1/8"	1/8"
Table Height	37-1/2"	37-1/2"
Brush Roller Motor (One Set)	1/2HP	1HP
Air Requirements	80 PSI	80 PSI
Abrasive Belt Dimensions	75"L x 36"W	75"L x 43"W
Main Motor (x2)	20HP/15HP, 3Ph, 220/440V Prewired 220V	30HP/20HP, 3Ph, 220/440V Prewired 220V
Conveyor Motor	2HP, 3Ph 220/440V Prewired 220V	3HP, 3Ph 220/440V Prewired 220V
Table Height Motor/Digital Readout	1/2HP	1/2HP
Net Weight	5,732 lbs	6,614 lbs



HEAVY DUTY double head configuration.